


CPT-SHR600HD3

HD1080P - 60fps High Speedy LPC camera

- ◆ Super H-IR Integrated IR illuminator LPC camera.
- ◆ Full High Definition 1080P@60fps.
- ◆ Full day to identification 150KM plate number over 98%.
- ◆ Defog function (Hi/ Middle/ Low) to strongly take number.
- ◆ Video stream UDP/TCP/HTTP/Multicast.
- ◆ LED illuminator is separate optical lens and camera.
- ◆ Reverse pressure tunnel, avoid dust & water adhesion.
- ◆ Acceptable Light Level control and synchronize camera video.
- ◆ Dual spectrum filter for day/night ICR exchange.
- ◆ Synchronize auto/manual/external/CDS sensor/LED linking and ICR.
- ◆ Built in SD storage, supporting alarm trig and off line application.
- ◆ Long life MTBF >20,000 hours.
- ◆ Weather proof IP68 grade.



HD IP Camera		CPT-SHR600HD3	
image sensor	1/2.8" SONY Exmor CMOS Sensor	DI/DO	2-alarm input / 2-alarm output
processor	ARM9 32bit SoC	alarm out	TCP,HTTP,SMTP, FTP
memory	RAM: 256MB, ROM: 512MB	alarm status	Pre-Alarm and Post-Alarm by configurable
Stream	Triple Stream	SH-IR LED CPT-X5IR	
duplex audio	G.711, 64 kbps, u-Law , A-Law	project distance	120 meter
sensitivity	0.01Lux, F1.4	recommend	20~25 meter in speed 150KM/per hours
resolution	HD1080P: 1920 x 1080 @60fps	IR spectre	850nm
Snapshot	Yes	project angle	12~25 degree
s/n ratio	> 58dB (AGC off, AESC off, Y sig.)	LED type	SH-IR LED
compress	H.264 / M-JPEG (Triple-stream)	isolate sunshield	dual sunshield
LAN port	RJ45, 10/100M	CDS sensor	20lux +- 5
Video	Full Screen Monitoring, AVI, JPEG	CDS level	VR-trimmer
Bit Rate	CBR, VBR 128k-16M	GPIO output	NC / COM / NO
speed shutter	1/30~1/10,000 , Auto	illumination	150Lux/20M
white balance	Auto, Manual, Saturation, Hue	IR LENS	
BL SET	2 AREA , HBLC , BLC , OFF	Lens type	5-50mm, 5-100mm
Day&Night	Color , B/W , EXT , AUTO	IR coating	clear picture and variorum picture
Day & Night	MFDN, ICR filter excgange,	f. stop	F / 1:1.4
Motion	3 different zone	mount mode	D14 mount
picture	contrast/ level/ sharpness/ GAMMA	Mechanic and Performance	
mirror	hor. ver. reverse function	power source	90~260VAC
ROI	clip picture for save bandwidth	consumption	22W
remote	RS232 , RS-485 (PELCO D)	clean glass	reverse pressure tunnel, avoid dust & water adhesion.
Privancy	3 different zone	hor. adjustment	optional-camera hor. position mechanic
WDR	wide dynamic range ON-OFF	casing structure	aluminum alloy
ID display	time-date and character	installation	clamshell open
LAN protocol	TCP,UDP,DHCP,RTP,RTSP,HTTP,NTP,UPnP, DDNS,PPPoE,SMTP,SNMP.Bonjour,FTP.	humidity	0 to 95% relative · non-condensing.
ONVIF	yes	connector	metal bundle
Triggered	Action in Mail, FTP, SD card, DO, Samba	heat sink	aluminum body
browser	IE, Firefox, Chrome, Safari.	weather grade	IP-68
Security	password, IP filter, HTTPS, Encrypted, 802.1x	dimension	159(W) x 173(H) x 435(L) mm , 4.2 Kg
password	yes	temperature	operaton:-15°C ~+60°C, storage:-30°C ~+70°C
Connection	Simultaneous up to 10		