

CPT- NRAF04/09 NVR Specifications



Main Features :

1. H.264 decompression format support.
2. Real-time Display & Playback.
3. Support Mega Pixel Camera for each channel.
4. Support CMS (Central Management System)
5. Audio Backup / Audio Streaming.
6. Graphic User Interface (GUI).
7. Support time-point backup function under Ethernet remote control mode. User can select any time period to process backup from remote side.
8. Support time-search & event-search function under Ethernet remote control mode.
9. Up to four online clients for independent remote control; individual live-time, play-back & time-search function available
10. Support PPPoE/ Static/ DHCP IP & DDNS.
11. Powerful mobile surveillance function, support JAVA 、blackberry 、iPhone & Windows mobile
12. Support log function

HNR- 04/09AF NVR Specifications

MODEL	CPT-NRAF4	CPT-NRAF9
VIDEO		
MODE	Multiplex	
DISPLAY CHANNEL	4Ch	9Ch
SUPPORT IP CAM RESOLUTION	Up to 1080P (2 M-pixel)	
DISPLAY FRAME RATE	Up to 30 FPS @ NTSC per CH	
SPLIT SCREEN	1, 4	1, 4, 9
VIDEO OUTPUT (VGA)	Yes	
AUDIO		
AUDIO OUTPUT	Phone Jack x 1	
AUDIO INPUT	Phone Jack x 1	
AUDIO BACKUP	Yes	
AUDIO STREAMING	Yes	
RECORDING		
COMPRESSION TYPE	H.264	
RECORDING RATE	Up to 30 FPS @ NTSC per CH	
RECORDING MODE	Manual / Schedule / Alarm	
PLAYBACK & SEARCH		
PLAYBACK SPEED	Fast Forward X 2, X4, X 8, X 16, X32 Fast Backward X 2, X4, X 8 Picture by Picture Playback Pause	
TIME SEARCH	Yes	
EVENT SEARCH	Yes	
OSD & CONTROL INTERFACE		
ON SCREEN DISPLAY & SETUP	Time / Date / Setup Menu	
GRAPHIC USER INTERFACE (GUI)	Yes	
MOUSE	Yes	
IE BROWSER	Yes	
PLAYER	Yes	

STORAGE & BACKUP DEVICE		
INTERNAL HDD SUPPORT	SATA HDD x 2	SATA HDD x 4
EXTERNAL USB BACKUP DEVICE (HDD, BURNER)	Yes	
NETWORK		
ETHERNET	Yes (1G)	
IE REMOTE CONTROL	Yes	
DDNS	Yes	
NTP	Yes	
E-MAIL & FTP	Yes	
NETWORK IP	Static/ Dynamic/ PPPoE /DDNS	
MULTI-REMOTE CLIENT	Yes (4 Clients at the same time available)	
ALARM		
ALARM INPUT	2 In	8 In
ALARM OUTPUT	2 Out (NO/ NC)	
MOTION DETECTION	Yes	
MOTION DETECTION AREA	Yes	
MOTION DETECTION SENSITIVITY	1-10	
VIDEO LOSS DETECTION	Yes	
ALARM RECORDING	Yes	
PRE-ALARM RECORDING	Yes	No
BUZZER	Yes	
SETUP & OTHER FUNCTIONS		
DAYLIGHT SAVING TIME	Yes	
WATER MARK	Yes	
PRIVACY MASK	Yes	
PTZ CONTROL	Yes	
RS-485	Yes	
DIGITAL ZOOM	Yes	
PASSWORD CONTROL	Two levels, one for system and the other for HDD format	
KEY-LOCK	Yes	
MULTI-LANGUAGE	Yes	
FIRMWARE UPDATE	USB Host & Update on line	

Others	
POWER INPUT	DC 12V
DIMENSIONS (W x H x D)	370mm X 60mm X 311mm
OPERATION TEMPERATURE	0 - 45 °C