

Weather Proof Heavy duty
Pan/Tilt Driver

CPT-AP115T

SPECIFICATION

Approval	Compliant to CE
Environmental standard	Compliant to IEC529 Dust –proof, water-proof IP-55 international standard
Rotation angle	Horizontal Pan : 0° ~ 355° Vertical Tilt : ±90° (Max. ±95°)
Rotation mode	Auto Pan feature
Loading capacity	Upright installation 60 Kg/132Lb ,
Balancing	Lead block on both hands of P/T
Rotating speed	Horizontal Pan : 6° /sec. , Vertical Tilt : 6° /sec.
Protection ambient	Limit switch on Pan & tilt
Limit switch	Pan & Tilt are 15A 10 million cycle rating
Gears	Hardened steel
Safety protection	Built-in electronic recovery breaker, over heated or power surge shut down
Safety recovery	Auto power recovery when power surge or over heated corrected
Sealing structure	Rubber ring & gasket seals for all weather environmental protection.
Power cable	Fire-proof UL wire DIN 6pin detachable plug.
Power supply	AC24V/AC110V/AC220V , 50Hz/ 60Hz , 8W ´ 2
Body structure	Die-casting aluminum alloy housing , Ivory color
Optional Heater	Option : Start :7°C(44.5°F) , Off :17°C(62.6°F)
Ambient temperature	Operation -26°C ~ 65°C (-15°F ~ 149°F) , Storage -30°C ~ 70°C
Mount plate dimension	Mount plate : 133x133mm , screw holes : 114x114mm 1/2" ø´x 4
Body dimension	247(W) x 324(H) x 156(D) mm, 13Kg

OPTIONAL VARIABLE SPEED MODEL ROTATION SPEED

Pan	0.15° to 13° /sec
Tilt	0.15° to 13° /sec.



Features & Characteristic:

- * Weather proof standard IP-55
- * Pan rotation angle: 0° ~ 355°, Tilt: ±95°
- * Available with optional preset function.
- * Optional Variable speed function
- * Hardened steel gear, for longest durability
- * Optional Chromium surface finishing for High corrosive or Acid environment
- * Heavy duty Loading, available for other peripherals I.e. IR lamp etc.

Model # description

CPT-AP115T /H	w/ Heater
CPT-AP115T /E	Chromium processed
CPT-AP115T /PS	Preset
CPT-AP115T /VS	Variable Speed for AC110 or AC220V
CPT-AP115T /VS24	Variable Speed for AC24V